

KEY FEATURES

- Intel® VIA™ C7 1.5GHz w/ 128KB Cache
- 1GB DDR2 Memory
- 15" Advanced Touch Screen Technology
- 160GB SATA HDD
- Energy efficient fan-free design
- Advance exchange (optional)
- Onsite Service (optional)
- Private label front bezel logo (option)



KS6200 Series

About Posiflex

Designer and manufacturer of Point-of-Service and industrial touch terminals

Revolutionary technology, reliable quality, reasonable pricing and recognized service

Delivers reliable terminals for maximum uptime and lower total cost of ownership

Comprehensive suite of peripherals and services

Over 25 years of innovative excellence

Global presence

Over 30 patents for innovation

Two ISO 9001/ 14001 Certified Facilities

Posiflex Fan-Free KS6215 Series

The KS6215 is our fan-free, high performance POS terminal that is available at a very attractive price point that you will love.

Not a limited offer, the KS6215 is a standard product featuring our patented aluminum chassis for maximum heat dissipation, a 1.5GHz CPU, Microsoft Windows XP or POS Ready or our special value bundle with Windows Embedded for Point of Service and a 2-track MSR. Available in a desktop configuration which easily converts to a wall mount solution. The KS6215 is ideally suited to end users looking for value and an attractive price with no compromise on quality.

Call today and find out how the KS6215 can boost your sales and help GROW your bottom line.

For more information call 888.968.1668 today!

Specifications

SPECIFICATIONS		KS6215	AVAILABLE SERVICES
Processor	Intel® VIA™ C7 1.5GHz, 128KB Cache		<ul style="list-style-type: none"> • Standard and Extended Warranty Extend your depot warranty up to 5 years. • Advance Exchange We ship overnight replacement equipment directly to your business. You return the faulty unit to Posiflex. • OnSite Service Expert technicians will efficiently handle the complete equipment swap and return process. • Regional Repair Depots Three regional depots assure fast turn-around time on repairs. • Post Warranty Support Spare parts, in addition to a flat rate repair program, for post warranty needs. • Installation Services Let our nationwide network of experts stage and install your equipment. • OEM Design and Integration Our Product Development Team helps design equipment, for custom hardware applications.
System Memory	DDR2 800 MHz, SO-DIMM socket x 1 (1GB Default)		
Maximum Memory	1GB with 32-Bit OS		
Power Supply	12V DC Power adaptor, 80W		
Storage Device	2.5" SATA 160GB HDD or SSD Kit (optional)		
Supported OS	POSReady / WinXP Pro / Linux		
DISPLAY			
LCD	15" TFT LCD, 1024x768		
Touch Function	5-Wire Resistive, USB Interface		
Brightness Control	Digital Push Button		
Tilt Adjustment	17.5° to 76.5°		
PHYSICAL DIMENSIONS			
Dimensions (WxDxH)	14.76" x 15.20" x 15.55"		
Weight (Pounds)	20 lbs		
CONNECTIVITY			
LAN Port	10/100/ Base-T Ethernet		
Serial Port	DB9 x 2		
Backup Battery Port	No		
RAID 1	No		
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD Monitor		
CR Port	CR x 1 (Controls 1 drawer)		
Standard USB Port(s)	4		
PERIPHERALS			

See www.posiflexusa.com for a complete line of peripherals

POSIFLEX™
 Be the Pioneer, Be the Leader
 30689 Huntwood Avenue
 Hayward, CA 94544
 Toll-free: 888.968.1668
 Phone: 510.429.7097
 Fax: 510.475.0982
 E-mail: sales@posiflexusa.com
www.posiflexusa.com

