



Touch Screen Infotainment Terminal

The HC-1521P is a high-end infotainment terminal with a 21.5 PCAP touch screen display. It offers real versatility for a variety of interactive solutions including self-service kiosks, kitchen display systems, and healthcare computing solutions.

About Posiflex

- Designer and manufacturer of Point-of-Service and industrial touch terminals
- Revolutionary technology, reliable quality, reasonable pricing and recognized service
- Delivers reliable terminals for maximum uptime and lower total cost of ownership
- Comprehensive suite of peripherals and services
- Innovative excellence since 1984 with more than 30 patents for innovation
- Global presence
- Two ISO 9001/9002/14001 Certified Facilities

Specifications

Processor	Intel Haswell Core i3-4330TE CPU, 2.40 GHz, 4M Cache; Intel Haswell Core i5-4570TE CPU, up to 3.30 GHz, 4M Cache
System Memory	DDR3L SO-DIMM x 2, max. 16GB in 2 slots
Storage Device	SATA x 1 + mSATA x 1
Power Supply	12V / 100W
OS support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request

Display & Touch

LCD Display	21.5" TFT LCD
LCD Resolution	1920 x 1080
Touch Function	True-flat PCAP touch with multi-touch support (IP65 on front panel)

I/O & Expansion

Serial Port	4, DB9 x 4, 5V/12V support on all COM ports
Parallel Port	N/A
Standard USB Port	7, USB 3.0 x 2+ USB 2.0 x 5
Powered USB	N/A
LAN Port	10/100/1000 Mb x 2
Display Port	VGA x 1 + HDMI x 1, 12V support on VGA port for Posiflex monitors
CR Port	N/A
PS/2 Keyboard	N/A
UPS Port	N/A
Camera	Front facing, 5MP, auto focusing
Audio	Internal 3W speaker x 2 + Mic-in/Line-out
Expansion Slot	mini-PCIe slot x 2
Hotkeys	Volume up, volume down, brightness up, brightness down, power (hotkeys lockable)

Physical Dimension

Dimension (W x D x H)	21.5" x 2.4" x 14.8"
Weight (lbs)	14.6

Environmental

Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

Built-in to Device

WiFi	Mini-PCIe WiFi/BT module
Scanner	2D barcode scanner

** The product information and specifications are subject to change without prior notice.