

Posiflex Adaptability

Posiflex touch screen terminals are over built, to over perform in harsh environments to assure maximum uptime. Your business is empowered with a well designed terminal, backed by solid service programs keep to your business running smoothly.

With global installations in a wide range of vertical markets Posiflex has met the touch screen terminal challenges from the smallest shop to the largest corporate environments.

Most operating environments, particularly retail and hospitality, can be demanding on take a toll on hardware. Posiflex's patented die-cast aluminum alloy chassis design efficiently diffuses heat, prolonging terminal longevity, and provides maximum uptime for profitability.



Posiflex works with best of breed kiosk partners to provide the ideal solution for your applications.

Our Kiosks options include:

- Wall mount
- Free standing
- Desktop
- ADA compliant

Posiflex touch screen technology is widely deployed in health care to not only reduce administration costs, but provide patient care and satisfaction. Terminals hardened against dust and liquids can be integrated with privacy filters to meet the exceptionally high standards of health care.

POSIFLEX™
Be the Pioneer, Be the Leader
30689 Huntwood Avenue
Hayward, CA 94544
Toll-free: 888.968.1668
www.posiflexusa.com

For Kiosks, Services, Healthcare and Product Datasheets, please visit www.posiflexusa.com



Posiflex Product Demonstrations

POSIFLEX™
Be the Pioneer, Be the Leader



Touch Screen Terminals

Posiflex designs, engineers and manufactures industrial grade terminals ranging from small electronic cash register replacements, to workstations, to back office servers with a full complement of printers, magnetic stripe readers, cash drawers and rear / pole displays.

Revolutionary Technology

- Over 30 design patents for product innovation, reliability and uptime.
- Over 25 years of engineering excellence and quality in two ISO 9001/9002/14001 certified facilities.
- Partner with software and hardware vendors to provide best of breed solutions.

Reliable Quality

- Best Product Winner for three years running - Business Solutions.
- Stringent third party HALT/HASS tested for extensive temperature cycling, vibration, drop, shock, static electricity and emission tolerance.
- Industrial grade components designed to not operate at 100%, minimizing heat and failure.
- Uncompromised fit and finish using die-cast aluminum alloy rather than plastic housing.
- Designed with no moving parts for fewer points of failure with the option of a solid state drive.
- Green consumption through 60% less power utilization than similarly specified PCs.
- Strict hardware revision control so the first terminal you purchase runs your application just like the last to maximize the terminal life cycle, reduce staging labor and minimize service costs.



Recognized Service

- Industry's first three year standard warranty
- Three North American depot service centers – Silicon Valley, Raleigh and Toronto, Canada.
- Full complement of service programs to assure business continuity.

POSIFLEX Selection Guide

Terminals			
Fan-Free Terminals XP Series	Fan-Free Terminals KS Series	Fan-Free Mini-PC TX Series	Terminals w/Fans TP Series
Sleek low profile and low cost electronic cash register (ECR) replacement with full POS terminal capability. Includes magnetic stripe reader and thermal receipt printer	The award winning product of choice for most applications. Exceptional fan free price / performance.	Mountable mini-PC which is ideal for small confined space or inside kiosks. Utilizes an external monitor.	Reliable platform for high performance applications
Intel® Atom™ D425 1.8GHz	Up to Intel® Core™ 2510E i5 2.5GHz	Intel® Atom™ D425 1.8GHz	Intel® Celeron® T3500 2.1GHz Dual Core Intel® Core™ 2 Duo P8400 2.26GHz
POSReady, POSReady 7, WinXP Pro, Win7 Pro and Linux Operating Systems			

UPOS Compliant Peripherals

Pole Displays	Keyboard Attachments	Magnetic Stripe Readers	Cash Drawers	Receipt Printers
Stand alone or terminal mounted, fixed or adjustable height	Up to 65 programmable keys Optional magnetic stripe reader	2-Track, 3-Track with or without biometric capability optional 3-Track encrypted MSR available	6 coin and 5 bill compartments, screwless tamper-resistant design	High speed, high resolution thermal printing

Services

Advance Exchange	Extended Warranty	Technical Support	Onsite Service	Installation
Overnight replacement	Up to 5 years Depot warranty coverage	10x5 phone support	Onsite Tech performs equipment swap and return	Stage and install equipment nationwide

POSIFLEX TOUCH TERMINAL TECHNOLOGY

FAN-FREE & ENERGY EFFICIENT

MODEL	XP3315	KS6715	KS6812	KS7200	KS7300	KS7700	TX3000	FANNED TP8315E		
Advantage	ECR Replacement w/Integrated Printer and MSR						Energy Efficient Fan Free Point of Service Terminals to Meet Every Price and Performance Point		Industrial grade Mini-PC CPU	High Performance
Processor	Intel® Atom™ D425 1.8GHz	VIA NANO™ 1.6GHz	Intel® Atom™ N270 1.6GHz	Intel® Atom™ D525 1.8GHz Dual Core	Intel® Celeron® M 1.86GHz	Intel® Core™ i3 2330E 2.2GHz Intel® Core™ i5 2510E 2.5GHz	Intel® Atom™ D425 1.8GHz	Intel® Celeron® T3500 2.1GHz Dual Core Intel® Core™ 2 Duo P8400 2.26GHz		
Cache	512KB L2	1MB L2	512KB L2	1MB L2	1MB L2	3MB L2	512KB L2	1MB L2 (T3500), 3MB L2 (P8400)		
Memory	1GB DDR3 SO-DIMM, MAX 4GB*	2GB DDR3 SO-DIMM, MAX 4GB	1GB DDR2 SO-DIMM, MAX 2GB	2GB DDR3 SO-DIMM, MAX 4GB	2GB DDR2 SO-DIMM, MAX 2GB	4GB DDR3 SO-DIMM, MAX 8GB	1GB DDR3 SO-DIMM, MAX 4GB	2GB DDR3 SO-DIMM, MAX 8GB		
Operating System	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady 7, Win XP Pro, Win 7 Pro, Linux ¹	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹	POSReady, POSReady 7, WinXP Pro, Win7 Pro, Linux ¹		
LCD Display	15" TFT LCD [1024x768]	15" TFT LCD [1024x768]	12" w/ LED bright backlight [1024x768]	15" TFT LCD [1024x768] 17" TFT LCD [1280x1024]	15" TFT LCD [1024x768] 17" TFT LCD [1280x1024]	15" TFT LCD [1024x768]	Compatible with all touch monitors and LCD displays	15" TFT LCD [1024x768]		
Tilt Adjustment	14° to 55°	15° to 70°	20° to 90°	15° to 70°	15° to 70°	15° to 70°	Dependent on touch monitor or LCD display selected	15° to 70°		
Touch Sensor	Resistive	Resistive	Resistive	Resistive or Infrared	Resistive or Infrared	Projective Capacitive with precision-edge design, Resistive, or Infrared	Optional Posiflex Touch Monitors Available	Resistive or Infrared		
Inclusive	Integrated 3" thermal printer 2 or 3 track MSR									
Storage	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD x2	160 GB 2.5" SATA HDD	160 GB 2.5" SATA HDD		
Ports	1 x RJ-45 10/100/1000 Base T Ethernet; 2 x 9-pin male d-sub; 1 x RJ-50; 1 x VGA 15-pin female d-sub; 4 x USB 2.0 Type A port; 1 x RJ-11 (controls two cash drawers); 1 x Backup battery;	1 x RJ-45 10/100/1000 Base T Ethernet; 4 x 9-pin male d-sub; 1 x VGA 15-pin female d-sub; 6 x USB 2.0 Type A port; 1 x RJ-11 (controls 2 cash drawers); Parallel Port*	1 x RJ-45 10/100/1000 Base T Ethernet; 2 x 9-pin male d-sub; 1 x RJ-50; 1 x VGA 15-pin female d-sub; 6 x USB 2.0 Type A port; 1 x RJ-11 (controls 2 cash drawers)	1 x RJ-45 10/100/1000 Base T Ethernet; 2 x 9-pin male d-sub; 2 x RJ-50; 1 x VGA 15-pin female d-sub; 6 x USB 2.0 Type A port; 1 x RJ-11 (controls 2 cash drawers); RAID 1 (optional); Parallel Port*	1 x RJ-45 10/100/1000 Base T Ethernet; 4 x 9-pin male d-sub; 1 x VGA 15-pin female d-sub; 6 x USB 2.0 Type A port; 1 x RJ-11 (controls 2 cash drawers); 1 x Backup battery; 1 x Mic in; 1 x Line out; 1 x 25-pin female d-sub	1 x RJ-45 10/100/1000 Base T Ethernet; 3 x 9-pin male d-sub; 1 x RJ-50 1 x VGA 15-pin female d-sub; 7 x USB 2.0 Type A port; 1 x RJ-11 (controls 2 cash drawers); 1 x Backup battery; 1 x Line out; RAID 1; Parallel Port*	1 x RJ-45 10/100/1000 Base T Ethernet; 3 x 9-pin male d-sub; 1 x RJ-50; 1 x VGA 15-pin female d-sub; 4 x USB 2.0 Type A port; 1 x PS/2 Port; 1 x RJ-11 (controls 2 cash drawers)	1 x RJ-45 10/100/1000 Base T Ethernet; 4 x 9-pin male d-sub; 1 x VGA 15-pin female d-sub; 5 x USB 2.0 Type A port; 1 x PS/2 Port; 1 x RJ-11 (controls 2 cash drawers); RAID 1 (optional); 1 x 25-pin female d-sub		

¹Only driver support is available for Linux | *Option available through cable P/N 21862033420

EXTERNAL PERIPHERALS

Secondary Displays

Stand alone or terminal mounted, fixed or adjustable height



PD2602 / PD308



PD2604 / PD3100



LM6101B / LM6601B



LM2312

Keyboard Attachments

Up to 65 programmable Keys;
Optional magnetic stripe reader



KP100



KP301

Magnetic Stripe Readers

2 or 3 track, with or without fingerprint or encryption



SD402



SD200



SD404



SD500W

Cash Drawers

6 coin and 5 bill compartments,
screwless, tamper resistant design



CR3100
adjustable coin slot
[15.7"W x 16.3"D x 3.5"H]



CR6300
fixed coin slot
[16.85"W x 18.11"D x 3.94"H]




Receipt Printer

High speed, high resolution
thermal printing



PP8000
[2-in-1: Serial / Parallel;
OR 3-in-1: Serial / Parallel /
USB or LAN]



PP6800
Low cost, high value
[Available in Serial,
Parallel, or USB]



SERVICES

Advance Exchange

Overnight replacement

Extended Warranty

Up to 5 years of total coverage

Technical Support

10x5 Phone Support

OnSite Service

OnSite Tech performs equipment swap and return

Installation

Stage and install equipment nationwide

POSIFLEX
Be the Pioneer, Be the Leader

For more information call
888.968.1668